

# SONALIKA - 26



**POWERED  
TO  
PERFORM**

|                               | Specifications   | SONALIKA - 26   |
|-------------------------------|--|---|
| Engine                        | Engine Type<br>HP Category<br>No. of Cylinders<br>Aspiration<br>Cubic Capacity (cc)<br>Rated RPM (+/-25mm)<br>Air cleaner<br>Cold Start<br>Max Torque @ RPM(Nm)<br>Exhaust | 3 cylinder, Mitsubishi S3L2,4,water cooled, vertical overhead valve, in line swirl chamber type<br>26 HP<br>3<br>Naturally Aspirated<br>1318cc<br>2700<br>Dry type<br>Yes<br>75.2@2200<br>Underhood Downdraft silencer  |
| Transmission                  | Drive<br>Clutch<br>Gearbox<br>Front Axle<br>Transmission   | 4WD<br>Single clutch<br>Sliding mesh<br>4 WD<br>6F+2R   |
| Speed (Forward)               | Maximum Speed (Km/Hr)<br>Minimum Speed (Km/Hr)   | 17.05<br>1.53   |
| Brakes                        | Brakes<br>Type of actuation<br>Trailer Brake<br>Hand brake   | OIB<br>Mechanically actuated<br>No<br>Yes, Latch Type   |
| Differential lock             | Differential lock  | Yes, Foot Operated  |
| PTO                           | PTO (rpm)<br>PTO (actuation)   | 540 @ 2080 ERPM , 540 E @ 1410ERPM, 1000 @ 1514ERPM<br>Mechanically actuated  |
| Steering                      | Steering   | Power steering  |
| Electrical                    | Battery<br>Alternator<br>Seven pin trailer socket  | 12V,50A<br>12V,40A<br>Yes   |
| Hydraulics                    | 3 point linkage<br>Stay Bars<br>Hydraulic lifting capacity<br>Auxiliary hydraulic circuit<br>Liftomatic<br>Lift rods   | Yes , Cat-1N<br>No, available with anchor chains<br>600Kg<br>1DA<br>No<br>Adjustable lift rods  |
| Safety Switch                 | Clutch Safety Switch<br>PTO Safety Switch<br>Neutral safety switch   | Yes<br>No<br>No   |
| Capacity (ltrs)(+/-5%) approx | Fuel tank (Lt)<br>Engine Oil (Lt)  | 30lts<br>4.2lts   |
| Turning Diameter              | Turning diameter With Brakes (m)<br>Turning diameter Without Brakes(m)   | 5.54<br>6.35  |
| Tyre                          | Front<br>Rear  | 6-12<br>8.3-20  |
| Dimension & Weight(+/-5%)     | Weight (kg)<br>Wheel Base (mm)<br>Total Length (mm)<br>Total Width (mm)<br>Height (mm)<br>Min Ground Clearance (mm) min<br>Front Track (mm)<br>Rear Track (mm)             | 1055Kg<br>1560mm<br>2705mm<br>1058mm<br>2153mm with ROPS<br>225mm (Front axle lower pt)<br>894mm<br>825mm   |
| Others                        | Fuel Indicator gauge<br>Front Toe Hook<br>Front weight<br>Trailer hitch<br>ROPS<br>FOPS<br>Drawbar   | Yes<br>Yes<br>Front wts- (15x2)<br>Fixed Trailer Hitch<br>Yes, E-Marked with detachable Beacon light<br>No<br>Yes   |
| Optional Features             | Optional Tyres   | 1. Agriculture tyres: Front tyre: 6-12<br>Rear tyre: 8.3-20<br>2. Turf tyres: Front tyre: 23x8.50-12LG 306 12PR TL<br>Rear tyre-33x15.50-16.5 LG 306 10PR TL<br>3. Industrial tyres: Front tyre-23x8.50-12 SPHD 12PR TL<br>Rear tyre-31x15.50-15 SPHD10 PR TL |
|                               | Cabin  | Heater only   |

## International Tractors Limited

H.O: Plot No. 29 and 31, Aggarwal Mall, CBD Ground, Near Karkardooma Court,  
Behind Hotel Kempenski, Delhi-110032 (India). **Phone:** +91 11 22600700, Fax: +91 11 22377472  
**Works:** Jalandhar Road, Hoshiarpur-146022, Punjab (India). **Phone:** +91 1882 302220, 302221,  
**Fax:** +91 1882 302293, **E-mail:** exports@sonalika.com , **Website:** www.sonalika.com.

Follow us on [www.facebook.com/SonalikaTractor](https://www.facebook.com/SonalikaTractor) | [www.twitter.com/SonalikaTractor](https://www.twitter.com/SonalikaTractor) | [www.linkedin.com/groups/Sonalika-Tractor](https://www.linkedin.com/groups/Sonalika-Tractor)