



# YANMAR



## DIESEL POWER TILLER YZC - D ( 11.0 HP )



**Tail Skid  
Standard Attachment**

## YZC - D ( 11.0 HP )

### **Tough, Economical engine**

YZC-D powered by water cooled, direct injection Yanmar diesel engine which are proven tough and low fuel consumption. The standard component, unique dual balancer shaft on this diesel engine model could reduce vibration and increasing the stability.

### **Multipurpose Usage**

YZC-D built to handle tilling, plowing and transportation purpose and more. With a direct transmission change make the 3 (three) forward and 1 (one) reverse gear changing smoothly.

### **Safe and Easy to Operate**

Main clutch and dry internal expansion brake joint together to increase the safety operational. It is easily to stopped even though the gears are still in need.

### **Suitable for Various Field Condition**

The tilling width could be adjusted for light till rough field by utilizing the 4 (four) speeds in order to suited the YZC-D with any tilling purpose

### **Easy to Connect and Disconnect the Attachment**

Simple and easy operation needed to connect and disconnect the attachment

### **Reverse Gear cannot be Engaged when the Rotary Operate**

Reverse gear can be engaged when the PTO (Power Take Off) is in the neutral position. This is to prevent the rotary from the accidentally engaged.

**PT. YANMAR AGRICULTURAL MACHINERY MANUFACTURING INDONESIA**



# YANMAR DIESEL POWER TILLER

## Features of Yanmar Diesel Power Tiller

1. To answer your demand, YANMAR offers you the stronger diesel power tiller.
2. Utilizing a trust-worthy construction system, you may no doubt its working capability and power as every part of the machine has been improved through dozens of year of experience.
3. A new-type of main mover with direct injection system installed in the YANMAR diesel power tiller produce constant and stronger power.
4. The main mover with the power tiller's compact and reinforced body makes your YANMAR diesel power tiller operate more smoothly and safely.
5. Another feature is brighter illuminating headlights that providing convenience work at night.

## Specifications

Model	unit	YZC-D	
Type		Rotary	
Dimensions with tire	Overall length	mm	2133
	Overall width	mm	800 857
	Overall height	mm	1210 1230
Engine	Model	TF110ML	
	Type	Horizontal, Water cooled diesel engine	
	Rated continuous output	hp/rpm	10.0/2400
	Maximum output	hp/rpm	11.0/2400
	Displacement	ltr	0.583
Weight with engine	Cooling system	Radiator	
	Fuel oil tank capacity	ltr	11.0
Transmission		kg	342 350
	Forward		3
Travel speed with rubber Tire	Reverse		1
	F1	km/h	1.03 1.24
	F2	km/h	2.14 2.57
	F3	km/h	7.15 8.57
	R	km/h	0,78 0,94
Rotary	Tilling method	Center Drive	
	Gear shifting	2 ( 4 ; Changed Sprocked )	
	Tilling width	mm	660
	Number of tines	pcs	18
	Tilling capacity	m2/hr	700 - 1200
Tire Tread		mm	5.00 - 12 607 ; 723

\* All data should be changed without prior notice.

## Optional Attachment

## Transportation

### Wet Paddy Field



SWAMP IRON WHEEL



CAGE WHEEL SPECIAL

### Dry Field




PLOWING WHEEL



SINGLE PLOW



RIDGER



TRAILER

PT. YANMAR AGRICULTURAL MACHINERY MANUFACTURING INDONESIA (PT. YAMINDO)

Head Office & Factory : Pandaan, Kabupaten Pasuruan Jawa Timur, Phone : 62-21-631316-62, 632435-37, Fax : 62-21-631363 e-mail : ymdfct@indo.net.id  
 Representative : Jalan .lr. H Juanda 42 Jakarta 10120 - Indonesia, Phone : 62-21-3456237, 3858066 (Hunting), Fax : 62-21-3813814  
 e-mail : ymdfct@indo.net.id